

TCMC

雙連式可變容量輪葉泵浦

VARI-DISPLACEMENT TWIN VANE PUMPS

TCVVP-F2323, F2626, F3030, F4040



特點：

- 本系列泵浦，操作時嘈音小，運轉滑順耐磨耗，適用於工作母機及專用機使用。
- 溫昇小，馬力損失小，內藏式自動壓力補償設計。

FEATURES:

- This series pump which being with low noise level, running smoothly and wear resistant, Especially, those are very suitable for machine tool & special purpose m/c use.
- Little temp upward & little power lose and designed of auto emerged pressure compensating.

訂購索引

ORDERING INDEX

TCVVP - F ※ ※ - A ※ - A ※ - 02

設計號碼 Design no.

壓力範圍 Pressure range(蓋端 Cover end)

1:5~18 bar, 2:15~35 bar

3:30~55 bar, 4:50~70 bar

壓力範圍 Pressure range(軸端 Shaft end)

1:5~18 bar, 2:15~35 bar

3:30~55 bar, 4:50~70 bar

吐出能力 Delivery capacity(蓋端 Cover end)

1:8(23)L/min, 2:12(26)L/min, 3:15(30)L/min, 4:20(40)L/min

吐出能力 Delivery capacity(軸端 Shaft end)

1:8(23)L/min, 2:12(26)L/min, 3:15(30)L/min, 4:20(40)L/min

安裝方式 Mounting style

F:Flange mounting(法蘭式)

系列號碼 Serial no.

規格

SPECIFICATIONS

型式 Model	吐出能力 Delivery capacity (1800 rpm)		壓力調整範圍 Pressure adj. range	額定速度 Rated speed	
	前泵 Front pump	後泵 Rear pump		最高 Max.	最低 Min.
TCVVP-F2323	23 l/min	23 l/min	5~18 bar 15~35 bar 30~55 bar 50~70 bar	1800 rpm	800 rpm
TCVVP-F2626	26 l/min	26 l/min			
TCVVP-F3030	30 l/min	30 l/min			
TCVVP-F4040	40 l/min	40 l/min			

■ 尺寸圖 DIMENSIONS

TCVVP-F2323, F2626, F3030, F4040

