

TCMC

可變容量輪葉泵浦 + 齒輪泵浦 VARI-DISP. VANE PUMPS & GEAR PUMPS TCVG-F23, F26, F30, F40 + PA



特點：

- 共用同一心軸及馬達，節省空間，本組合泵因採用一小流量之齒輪泵，而形成一高低泵組合。
- 噪音小、效率高，運轉滑順。

FEATURES:

- Employed same shaft & motor, save occupied space. Since, this combination pump is adopted a small flow rate gear pump and formed a hi-low pressure pump set.
- Low noise level, hi-efficiency, and running smoothly.

訂購索引

ORDERING INDEX

TCVG - F※ - A※ - G※ - 02

設計號碼 Design no.

吐出能力 Delivery capacity(齒輪泵 Gear pump)
PA₁, PA₂, PA₆, HR₁, HR₂(2~12c.c/rev.)

壓力範圍 Pressure range
1:5~18 bar, 2:15~35 bar
3:30~55 bar, 4:50~70 bar

吐出能力 Delivery capacity(可變容量輪葉泵 Vari-disp. vane pump)
1:23L/min, 2:26L/min, 3:30L/min, 4:40L/min

安裝方式 Mounting style
F: Flange mounting(法蘭式)

系列號碼 Serial no.

規格

SPECIFICATIONS

型式 Model	齒輪泵 Gear pump		可變量泵 Vari-disp. vane pump		額定速度 Rated speed	
	最大壓力 Max. pres.	吐出能力 Deliv. Cap.	最大壓力 Max. pres.	吐出能力 Deliv. Cap.	最高 Max.	最低 Min.
TCVG-F23	3000psi	2~12c.c/rev.	1000psi	23L/min	1800 rpm	800 rpm
TCVG-F26				26L/min		
TCVG-F30				30L/min		
TCVG-F40				40L/min		

■ 尺寸圖 DIMENSIONS

TCVG-F23, F26, F30, F40+PA

